


SIRIUS

T5 Direct-Indirect Recessed Luminaire



Type:	Unique direct-indirect recessed T5 luminaire that incorporates the latest technology of Class A High Frequency Helvar Control gear, giving maximum efficiency, energy saving and quality of light. Outstanding design and look. One of the most elegant recessed luminaires on the market with superior lighting performance. Lightweight at just 1.8 kg with a height of only 66 mm.
Specification:	A combination of two aluminum curved reflectors for indirect light projection and a double parabolic specular aluminum louvre, for direct light projection, with specular inserts to give better light distribution. The louvre is fitted into the body with four spring locks for maximum stability. Deluxe version louvres are manufactured using Alanod MIRO aluminum with 95% reflectiveness. Fully enclosed white steel body. Deluxe version made completely of specular aluminum. Luminaire is plastic-wrapped and packaged in twin boxes.
Installation:	Fits 15–24 mm exposed T-Bar ceilings and/or plasterboard ceilings. When the luminaire is fitted into a plasterboard ceiling, it is recommended to use support brackets.
Application:	Office buildings, shops and other commercial environments.



SB – Support brackets (4 pcs) for installation into a plasterboard ceiling. Available on request

Type	Lamp (W) and holder	Overall dimensions, mm	Weight, kg	Total wattage, W
Sirius 224 B37	2×24 (G5)	595×595×66	1,8	49
Sirius 414 A03	4×14 (G5)	595×595×66	1,8	62
Sirius 424 D59	4×24 (G5)	595×595×66	2,1	98
Sirius 224 B37 Deluxe	2×24 (G5)	595×595×66	1,8	49
Sirius 414 A03 Deluxe	4×14 (G5)	595×595×66	1,8	62
Sirius 424 D59 Deluxe	4×24 (G5)	595×595×66	2,1	98

Options available on request:

DIM – Dimmable ballast 1-10V

SWITCHDIM – Switch DIM ballast

DALI – DALI ballasts

EMG – Emergency version 1 hour

EM2 – Emergency version 2 hours

EM3 – Emergency version 3 hours

4TB – 4 way terminal block for loop feed and ease of wiring

5TB – 5 way terminal block with two holes (for in and out going cable)

MAT – Matt reflector (subject to minimum order)

MRO – Reflector Deluxe

PMT – Matt perforated inserts (subject to minimum order)

MTO – Matt reflector Deluxe (subject to minimum order)

SMS – Glossy aluminum body

WIE – 3-poles connector (subject to minimum order)

W625 – Designed for the German market to fit 625×625 suspended ceiling

Deluxe – MIRO® aluminum louvre and matt aluminum body

SIRIUS 224 B37 DELUXE

