

JETTA

Recessed Indirect Luminaire



Type: Modern design Indirect LED or CFL luminaire with light source hidden under a perforated diffuser. The light is reflected across the two parabolic reflectors to allow a comfortable and glare-free lighting effect.

Specification: A white painted perforated diffuser with UV stable opal film to give soft light distribution. Two parabolic reflectors. Fully enclosed white steel body. Luminaire is plastic-wrapped and packaged in twin boxes.

Installation: Fits 15-24mm exposed T-Bar ceilings 600x600mm.

Application: Office buildings, shops and other commercial environments.

Type	Lamp (W) and holder	Overall dimensions, mm	Weight, kg	Total wattage, W
Jetta 236 C49	2x36 (2G11)	595x595x100	4	84
Jetta 240 B44	2x40 (2G11)	595x595x100	4	84
Jetta 255 B40	2x55 (2G11)	595x595x100	4	118

Type	Overall dimensions, mm	Luminous flux, lm	Color temperature, K	Color rendering, Ra	Total wattage, W	Weight, kg
Jetta R LED4x1050 B336 T840	595x595x100	4200	4000	>80	31	4
Jetta R LED4x1400 B337 T840	595x595x100	5600	4000	>80	46	4
Jetta R LED4x2000 B338 T840	595x595x100	8000	4000	>80	66	4

Options available on request:

HF	– High Frequency control gear
DIM	– Dimmable ballast 1-10V
SWITCHDIM	– Switch DIM ballast
DALI	– DALI ballasts
EMG	– Emergency version 1 hour
EM2	– Emergency version 2 hours
EM3	– Emergency version 3 hours
WIE	– 3- poles connector Wieland or similar connectors
T830	– Color temperature 3000K
T840	– Color temperature 4000K
T857	– Color temperature 5700K

JETTA 255 B40

