




BALI T5&LED

**Recessed Frameless
Luminaire with Opal
Diffuser**



CE EAC



Type: Frameless recessed T5 or LED luminaire for installation into plasterboard ceiling.

Specification: UV stable opal diffuser mounted into frameless body.
Fully enclosed white steel body.
Luminaire is plastic-wrapped and boxed individually.

Installation: Fits into plasterboard ceiling.

Application: Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Bali R LED1x1000 D091 T840 OP LT80	215x225x80	50000	937	10	80+	4000	1,80
Bali R LED1x1400 D092 T840 OP LT80	215x225x80	50000	1317	14	80+	4000	1,80
Bali R LED1x1100 D093 T840 OP LT80	581x90x80	50000	1054	11	80+	4000	1,80
Bali R LED1x1500 D094 T840 OP LT80	581x90x80	50000	1480	15	80+	4000	1,80
Bali R LED1x1700 D095 T840 OP LT80	881x90x80	50000	1640	16	80+	4000	2,10
Bali R LED1x2400 D096 T840 OP LT80	881x90x80	50000	2302	24	80+	4000	2,10
Bali R LED1x2300 D097 T840 OP LT80	1181x90x80	50000	2225	22	80+	4000	2,40
Bali R LED1x3200 D098 T840 OP LT80	1181x90x80	50000	3124	30	80+	4000	2,40
Bali R LED1x2900 D099 T840 OP LT80	1481x90x80	50000	2811	28	80+	4000	2,80
Bali R LED1x4000 D100 T840 OP LT80	1481x90x80	50000	3946	38	80+	4000	2,80
Bali R LED1x3000 D101 T840 OP LT80	580x300x80	50000	2917	30	80+	4000	3,80
Bali R LED1x3700 D102 T840 OP LT80	580x300x80	50000	3658	40	80+	4000	3,80

* Tolerance range for optical and electrical data: ±10 %

Type	Lamp (W) and holder	Overall dimensions (Lx-WxH), mm	Weight, kg	Total wattage, W
Bali 213 M04 HF	2x13 (G24q-1)	205x215x80	1,8	28
Bali 218 M05 HF	2x18 (G24q-2)	205x215x80	1,8	40
Bali 226 M06 HF	2x26 (G24q-3)	205x215x80	1,8	55
Bali 114 M07	1x14 (G5)	580x90x80	1,8	16
Bali 124 M08	1x24 (G5)	580x90x80	1,8	25
Bali 121 M09	1x21 (G5)	880x90x80	2,1	23
Bali 128 M10	1x28 (G5)	1180x90x80	2,4	30,5
Bali 135 M11	1x35 (G5)	1480x90x80	2,8	38
Bali 139 M12	1x39 (G5)	880x90x80	2,4	42
Bali 149 M13	1x49 (G5)	1480x90x80	2,8	53
Bali 154 M14	1x54 (G5)	1180x90x80	2,4	58
Bali 180 M15	1x80 (G5)	1480x90x80	2,8	85
Bali 314 M16	3x14 (G5)	580x300x80	3,8	47
Bali 324 M17	3x24 (G5)	580x300x80	3,9	74
Bali 414 M18	4x14 (G5)	580x300x80	3,8	62
Bali 424 M19	4x24 (G5)	580x300x80	3,9	98

Options available on request:

- HF – High Frequency control gear
- DIM – Dimmable ballast 1-10V
- SDIM – Switch-control/dimming
- DALI – DALI driver
- TW – Tunable white
- BLT – Bluetooth unit (for wireless control via mobile device)
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- OP LT80 – Opal diffuser with 80% light transmission
- WIE – 3-pole Wieland or similar connector
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K

BALI R LED1X1400 D092 T840 OP LT80

