

TUCANA LED

Surface/Suspended
LED Luminaire for
Direct Illumination




Type: A low profile, surface mounted or suspended LED luminaire with double parabolic reflector for better glare control.

Specification: Double parabolic louvre made of glossy aluminium. UV stable opal diffuser. The louvre is fitted into the body with six spring locks for maximum stability. Fully enclosed white steel body with plastic end caps. Luminaire is boxed individually.

Installation: Surface luminaire is designed to be fixed to ceiling of any type or suspended.

Application: Indoor. Office buildings, shops and other commercial environments.



Wire suspension set (**SUSY**) and plastic cap with spiral cable (**CAPW**) are available on request.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Tucana LED1x2200 D305 T840	1260x175x52	50000	2134	21	80+	4000	3,20
Tucana LED1x3000 D306 T840	1260x175x52	50000	3000	29	80+	4000	3,20
Tucana LED1x4200 D307 T840	1260x175x52	50000	4160	41	80+	4000	3,20
Tucana LED1x2700 D308 T840	1562x175x52	50000	2696	26	80+	4000	3,80
Tucana LED1x3800 D309 T840	1562x175x52	50000	3790	36	80+	4000	3,80
Tucana LED1x5300 D310 T840	1562x175x52	50000	5254	52	80+	4000	3,80

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- PULLSWITCH – Pull switch device
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- 5TB – 5 way terminal block with two holes (for in and out going cable)

- 1LIN – Through wiring 3x1.5 mm² with two push-in terminal blocks
- 3LIN – Through wiring 5x1.5 mm² with two push-in terminal blocks
- SUS – Suspended version
- RAL – RAL colours
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K

TUCANA LED1X4200 D307 T840

