


AQUARIUS LED

Adjustable Circular LED Downlight



Type: A range of round adjustable circular LED downlights for accent lighting applications.

Specification: Aluminium faceted reflector with tempered glass. Light beam 60°. Body in cast aluminium in white finish. Removable gearbox with thermoplastic body. Luminaire is plastic-wrapped and boxed individually.

Installation: Suitable for plasterboard or similar types of ceiling, requires a cut-out.

Application: Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Aquarius LED1x1600 D323 T840 CLR	Ø185(177)x150	50000	1597	14	80+	4000	2,50
Aquarius LED1x2300 D324 T840 CLR	Ø185(177)x150	50000	2216	21	80+	4000	2,50
Aquarius LED1x3000 D325 T840 CLR	Ø185(177)x150	50000	2990	28	80+	4000	2,50

* Tolerance range for optical and electrical data: ±10 %

Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- CLR – Clear glass
- R36 – Reflector with 36° light beam angle (subject to minimum quantity)
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K
- RAL – RAL colours

AQUARIUS LED1X3000 D325 T840 CLR

