

# CORVUS LED

## Adjustable Square LED Downlight



**Type:** A range of square adjustable LED downlights for accent lighting applications.

**Specification:** Aluminium faceted reflector with tempered glass. Light beam 60°. Body in cast aluminium in white finish. Removable gearbox with thermoplastic body. Luminaire is plastic-wrapped and boxed individually.

**Installation:** Suitable for plasterboard or similar types of ceiling, requires a cut-out.

**Application:** Indoor. Decorative lighting for shops, displays, interiors, offices, receptions and other public areas.

Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Corvus LED1x1600 D326 T840 CLR	145x145(138x138)x115	50000	1597	14	80+	4000	2,00
Corvus LED1x2300 D327 T840 CLR	145x145(138x138)x115	50000	2216	21	80+	4000	2,00
Corvus LED1x3000 D328 T840 CLR	145x145(138x138)x115	50000	2990	28	80+	4000	2,00

\* Tolerance range for optical and electrical data: ±10 %

### Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- CLR – Clear glass
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K
- RAL – RAL colours

### CORVUS LED1X3000 D328 T840 CLR

