

CORONA Q LED



Recessed LED Luminaire with Square Diffuser



Type: A recessed mounted LED luminaire with square opal diffuser for most commercial lighting applications.

Specification: Diffuser: high transmission opal (OP LT80).
Fully enclosed white steel body.
Luminaire is plastic-wrapped and boxed individually.

Installation: Fits 15-24mm exposed T-Bar ceiling 600x600mm.

Application: Indoor. Office buildings, shops and other commercial environments.

Name	Overall dimensions (LxWxH), mm	Life-time	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Corona Q LED1x3200 E394 T840 OP LT80	595x595x70	50000	3144	31	80+	4000	5,00
Corona Q LED1x4500 E395 T840 OP LT80	595x595x70	50000	4416	45	80+	4000	5,00
Corona Q LED1x6400 E396 T840 OP LT80	595x595x70	50000	6311	61	80+	4000	5,00

* Tolerance range for optical and electrical data: $\pm 10\%$

Options available on request:

- SDIM – Switch-control/dimming
- DALI – DALI driver
- TW – Tunable white
- BLT – Bluetooth unit (for wireless control via mobile device)
- EMG – Emergency version 1 hour
- EM3 – Emergency version 3 hours
- OP LT80 – Opal diffuser with 80% light transmission
- W625 – To fit 625x625 suspended ceiling (subject to minimum quantity)
- IP44 – IP44 protection degree
- RAL – RAL colours
- T830 – Colour temperature 3000K
- T840 – Colour temperature 4000K

CORONA Q LED1X4500 E395 T840 OP LT80

