

SHOP M LED

Continuous Light Line
LED Luminaire



CEEC



SHOP M LED1X7400 D014 T840 LF90 LL

- Type:** A continuous light line LED luminaire to suit all retail and industrial applications.
- Specification:** Optical choice: 90° (standard), 30x90°, 60x110°, asymmetric and double asymmetric wide beam patterns.
Body and end caps in white steel.
Luminaire is plastic-wrapped and packed separately.
- Installation:** Suspended (suspension brackets are included). Through-wiring 5x1,5mm² with 5 pole plugs (5x2,5mm² on request).
- Application:** Indoor. Supermarkets, warehouses, production facilities and other commercial environments.



Through-wired version 5x1,5mm² with 5-pole connectors on both sides (male & female type). Quick installation features save project time and money. For more information check option list.



Supplied with two suspension brackets.

Name	Overall dimensions (LxWxH), mm	Lifetime	Luminaire output*, lm Ta=25°C	System power*, W	CRI (Ra)	CCT, K	Weight, kg
Shop M LED1x3000 D011 T840 LF90	1157,5x89x54	50000	2938	22	80+	4000	2,50
Shop M LED1x4100 D012 T840 LF90	1157,5x89x54	50000	4042	30	80+	4000	2,50
Shop M LED1x5200 D013 T840 LF90	1157,5x89x54	50000	5130	41	80+	4000	2,50
Shop M LED1x7400 D014 T840 LF90	2874x89x54	50000	7344	53	80+	4000	6,30
Shop M LED1x10200 D015 T840 LF90	2874x89x54	50000	10104	76	80+	4000	6,30
Shop M LED1x12900 D016 T840 LF90	2874x89x54	50000	12825	103	80+	4000	6,30


* Tolerance range for optical and electrical data: $\pm 10\%$

Versions with other lengths, light outputs or optics are available on request (subject to minimum quantity)


Options available on request:

SDIM	- Switch-control/dimming	LF60x110	- Optics with 60x110° beam angle
DALI	- DALI driver	LF30x90	- Optics with 30x90° beam angle
EMG	- Emergency version 1 hour	LF2AW	- Optics with double asymmetric wide beam pattern
EM3	- Emergency version 3 hours	LFA1	- Optics with asymmetric beam
1LIN2.5	- Through wiring 3x2.5 mm ² with two push-in terminals	RAL	- RAL colours
3LIN2.5	- Through wiring 5x2.5 mm ² with two push-in terminals	T830	- Colour temperature 3000K
L1	- Driver connected to L1 line	T840	- Colour temperature 4000K
L2	- Driver connected to L2 line	L	- For in-line connection end/first luminaire (lengths: 1155,5/ 2872mm)
L3	- Driver connected to L3 line	LL	- For in-line connection intermediate luminaire (lengths: 1153,5/ 2870mm)
LF90	- Optics with 90° beam angle		


SHOP M LED1X7400 D014 T840 LF90




SHOP M LED1X7400 D014 T840 LF60X110



SHOP M LED1X7400 D014 T840 LF30X90



SHOP M LED1X7400 D014 T840 LF2AW



SHOP M LED1X7400 D014 T840 LFA1

